



**Technical data**

Multiphase supply voltage	380 - 415 V 2N/3N
Single-phase supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	7,6 kW (4,4 kW / 3,6 kW)
Three-phase power supply/fuse protection	3 x 16 A (standard connection)
Two-phase power supply/fuse protection	2 x 16 A
Single-phase power supply/fuse protection	1 x 32 A (1 x 20 A / 1 x 16 A)
Dimensions (width x depth x height)	760 x 515 x 199 mm
Weight (incl. accessories/packaging)	24,5 kg
Surface material	SCHOTT CERAN®
Cooktop extractor power levels	1 - 9, P
Cooktop power levels	1 - 9, P
Size of exhaust opening	445 x 137 mm
Size of front cooking zone	Ø 210 mm
Size of rear cooking zone	Ø 175 mm
Front cooking zone output	2300 W
Rear cooking zone output	1400 W
Front cooking zone power setting output	3000 W
Rear cooking zone power setting output	2100 W
Filter medium	Activated charcoal filter with ion exchanger
Filter material	Filter panel with fine filter
Maximum filter service life	150 h (1 year)

**Product description**

- Intuitive sControl control
- eSwap
- effective odour removal
- Minimum volume
- Simple cleaning
- Integrated grease drip pan
- Oversized 4 24 cooking surface
- Maximum storage space
- Automatic extractor control
- Demo mode

**Scope of delivery**

- Induction cooktop with integrated cooktop extractor - recirculation PURU
- Air inlet nozzle black
- stainless steel grease filter
- activated charcoal filter
- operating and installation instructions
- drilling template
- Mounting clamps
- sealing tape
- height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply

**Accessories**

- Air inlet nozzle black PUED
- Air inlet nozzle greige PUEDG
- Air inlet nozzle red PUEDR
- Air inlet nozzle jade green PUEDJ
- Air inlet nozzle orange PUEDO
- Air inlet nozzle blue PUEDB
- Stainless steel grease filter PUEFG
- Activated charcoal filter PUAKF
- UDB25 sealing tape
- BKR760 cooktop frame
- Air purification box telescopic pull-out PULBTA

**product- and planning instructions**

- The connection cable must be provided at the installation site
- Front power socket
- The air purification box is fitted with a telescopic pull-out (extension to 80 mm) for connection to the back wall of the unit
- The telescopic extension of the air purification box in extra-deep cooktop base cabinets can be extended by 105 mm with an additional telescopic extension PULBTA (available as accessory)
- Ensure sufficient ventilation of the area below the cooktop.
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes
- Please note that induction-compatible cookware must be used on induction cooktops
- The PURE cooktop extractor system can be combined with all BORA sockets