



RW414365
Vario wine climate cabinet 400 series
fully integrated, with glass door
Niche width 45.7 cm, Niche height 213.4 cm



Two independantly controllable climate zones
 Consistant temperatures with exact control from +5 °C to +20 °C
 Humidity control
 Stainless steel interior
 Fully extendable bottle trays in oak wood and solid aluminium in anthracite
 Bottle trays with hidden telescopic rails
 Warm white and glare-free LED light spots
 5 preset lighting scenarios, selectable via TFT display
 Opening assist for door with two options:
 1. Push-to-open function for integration into handleless furniture front
 2. Pull-to-open function to facilitate opening the door using a handle
 Low-vibration operation
 TFT touch display
 Capacity 70 bottles

Handling
 TFT touch display operation.
 Clear text display.

Features
 Dynamic cold air distribution.
 Automatic defrosting with defrost water evaporation.
 Cushioned door closing system.
 Activated charcoal air filter.
 UV-protection.
 Rest mode certified by Star-K.
 When rest mode is active, the appliance can only be opened using a handle.
 Open-door and malfunction alarm.
 Integrated WiFi module for digital services (Home Connect).
 Light scenarios and temperature setting via Home Connect.
 The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Features
 Capacity 70 bottles (based on 0.75 l standard bottles).
 12 bottle trays,
 - 10 fully extendable trays
 - 3 suitable for storage of Magnum bottles.
 Flexible interior configuration possible by adding or removing fully extendable bottle trays.
 Storage of up to 6 Magnum bottles with standard tray configuration (12 bottle trays).
 Space for max. 13 bottle trays.
 2 brilliant LED light spots with warm white, glare-free light (3500 K) in each climate zone.
 5 different lighting scenarios can be selected for individual wine presentation.
 Total volume 272 litres.

Product rating
 Energy efficiency class G at a range of energy efficiency classes from A to G.
 Energy consumption 145 kWh/year.
 Noise level 42 dB (A) re 1 pW.

Planning notes

Characteristics
Energy Efficiency Class
 G
Average annual energy consumption in kilowatt hour per year (kWh/a)
 145
Capacity of 75 cl bottles
 70
Airborne acoustical noise emissions
 42
Airborne acoustical noise emission class
 D
Construction type
 Built-in
Door panel options
 Not possible
Height
 2125
Width of the appliance
 451
Depth of the product
 608
Required niche size for installation (HxWxD)
 2134.0 x 457.0 x 610
Net weight
 136.0
Connection rating
 300
Fuse protection
 10
Interior ventilator
 Yes
Voltage
 220-240
Frequency
 50-60
Approval certificates
 CE, VDE
Length of electrical supply cord
 300
Plug type
 Gardy plug w/ earthing
Number of compressors
 1
Number of independent cooling systems
 1
Reversible Door Hinge
 Yes
Interior light switch
 No
EAN code
 4242006290887
Brand
 Gaggenau
Product name / Commercial code
 RW414365
Product category

Consumption and connection features
 created on 2022-03-08
 Page 1

Flat hinge.
 Door hinge right, reversible.
 Door opening angle of 115°, fixable at 90°.
 Max. door panel weight 76 kg.
 The main socket needs to be planned outside of the niche.
 No Transport/operation above 2000m sea level

Connection
 Total connected load 0.300 KW.
 Connecting cable 3.0 m, pluggable.

Color Variants

RW414365
fully integrated, with glass door
Niche width 45.7 cm, Niche height 213.4 cm

Included accessories

1 x connection set.

Optional accessories

RA430000
 RA491161
 RA492160
Removable shelf with oak wood frame
 RA493060
 RA498140
Bottle support in oak wood for convenient storage of bottles on the division plate.

Installation Accessories

RA420010
 Door lock
 RA421111
 RA421112
 RA423140
 RA425110
Handle bar, stainless steel, long
 RA428111
 RA460013
 RA464111
Ventilation grille stainless steel

RW414365


Vario wine climate cabinet 400 series

fully integrated, with glass door


Niche width 45.7 cm, Niche height 213.4 cm

created on 2022-03-08


Page 2



The maximum door panel dimensions are based on a clearance of 3 mm.




Bottle storage



A: Suitable area for storage of magnum bottles in standard tray configuration
 B: 0.75 liter
 Measurements in mm


Wall clearance RB 472/RC/RF/RW



| Recess width | C | D | E1 | E2 |
|--------------|--------|--------|--------|----|
| 457 mm | 525 mm | 235 mm | 265 mm | |
| 610 mm | 677 mm | 299 mm | 330 mm | |
| 762 mm | 830 mm | 364 mm | 395 mm | |
| 914 mm | 980 mm | 428 mm | 460 mm | |


In the drawing, a unit front thickness of 19 mm and a Gaggenau unit handle of 49 mm were taken as a basis.

Door opening angle



The hinge travel and resulting clearances from adjacent furniture units and handles can be found from the drawing while allowing for the thickness of the front panel. In the drawing, a furniture unit front panel thickness of 19 mm was assumed.

Base detail



Based on the standard appliance height, the height of the plinth is 102 mm. Maximum plinth thickness 19 mm.